

# A Critical Review of Inlet-Outlet Valve Time Parameters used for Spark and Compression Ignition Engines

K. Ashok Reddy<sup>1</sup>, U. Susahni<sup>2</sup>, M. Mahinder Reddy<sup>3</sup>, G. Arun Reddy<sup>4</sup>

<sup>1</sup>Professor, <sup>2,3,4</sup>Assistant Professor  
Department of Mechanical Engineering,  
MLR Institute of Technology,  
Dundegal, Hyderabad -43 Teleganna State, India.

**Abstract:** We have reviewed technical, numerical and experimental papers of different investigators proposed new innovation ideas in the development of valve timing parameters for diesel and petrol engines single or multi cylinder two or four stroke engines in this paper. Development in advanced Variable Valve Actuation technology with Multi Air system and to improve engine performance parameters like specific fuel consumption, brake thermal efficiency and mechanical efficiency etc. in automobile industry, experiments were conducted by adjusting the valve lift and opening period in rocker arms and testing various follower configurations in a commercially-available rocker arm and made comparison was made different levels of valve lift and opening period in the intake and exhaust valves mechanism have reported in their technical papers. The development of a new exhaust rotary valve enabling the control of the opening independently from the control of the closure of the exhaust port based on kinetic and thermodynamic analysis in premixed combustion and heterogeneous compression combustion have been adopted to improve the control of emissions from automobile engines.

## Introduction:

Mateos Kassa et al [1] presented in their technical paper the impact of the intake valve timing on knock propensity is investigated on a dual-fuel SI engine leveraging a low octane fuel and a high octane fuel to adjust the fuel mixture's octane rating (RON) based on operating point. Variations in the intake valve timing have a direct impact on residual gases concentration due to valve overlap and changes in the compression pressure and temperature due to variations of the effective compression ratio. In this study, it was shown that the fuel RON requirement for a non-knocking condition at a fixed operating point can vary significantly solely due to variations of the intake valve timing. The fuel RON requirement at 2000 rpm and 6 bar BMEP ranges between 80 to 90 as a function of VVT, and between 98 to 104 at 2000 rpm and 14 bar BMEP.

Xianlin Ouyang et al [2] presented in their technical paper effective approaches for improving the gasoline engine fuel economy for both Atkinson and Miller cycles, the engine can be designed with a higher geometric compression ratio for increasing the expansion work and the effective compression ratio was governed by the intake valve close (IVC) timing for the knock control. Duration of the intake event and IVC timing affect not only the pumping loss during the gas exchange, but also have strong influences on the friction torques of the intake cams and the turbulence intensities for the in-cylinder charge motion. The latter governs duration of combustion and EGR tolerance, both of which have impacts on the engine thermal efficiency. Dojoong Kim et al [3] presented in their technical paper the development of an end pivot rocker arm type two-step VVA mechanism, in which single cam drives two valves. The mode conversion of the two-step variable mechanism is done by an electronic switching system instead of a conventional hydraulic system.

Luigi Teodosio et al [4] presented in their technical paper a promising technique to cope with the above drawbacks consists in the Variable Compression Ratio (VCR) concept. An optimal Compression Ratio (CR) selection, in fact, allows for further improvements of the thermodynamic efficiency at part load, while at high load, it permits to mitigate knock propensity, resulting in more optimized combustions.

Andrea Piano et al [5] presented in their technical paper a simulation for the impact of Variable Valve Actuation technology on the exhaust temperature of a modern light duty engine attached with a Variable Geometry Turbine. Mirko Baratta et al [6] presented

in their technical paper the development of a small displacement turbocharged engine, which combines the advanced Variable Valve Actuation technology MultiAir system for the air metering with the direct injection of natural gas. The activity focused on the development and fluid-dynamic characterization of the gaseous-fuel injector. Igor Trevas et al [7] presented in their technical paper a comparison between different way of actuation in combustion analysis of a Variable Valve Actuation system on a spark ignition engine. Guy Babbitt et al [8] presented in their technical paper an overview of the analysis and design of the Digital camless valve train including the architecture and design of the valve and head and the details of the electric valve actuator, and the flow characteristics of the valves and resulting charge motion in a motoring engine. The valve stroke provides the full flow area about 25% of the stroke of the equivalent poppet valve, thus saving electrical actuation with very low power consumption. Dileep Malkhede et al [9] presented in their technical paper a numerical model for the kinematic analysis of a continuous variable valve lift. It consists of eccentric shaft fitted with a series of intermediate rocker arm, which in turn control the degree of valve lift. The main characteristic of this mechanism was that it uses a general curve contact between the elements, which was determined using theory of envelope curve. Shinji Kasatori et al [10] presented in their technical paper the development of an

alloy of titanium exhaust valves and heat-resisting titanium alloy with high deformation resistance because of its superior strength at high temperature.

José Ramón Serrano et al [11] presented in their technical paper the influence of several design parameters was studied by modeling approach under steady state operating conditions in a Diesel engine. Jorge Martins et al [12] presented in their technical paper the development of a new exhaust rotary valve enabling the control of the opening independently from the control of the closure of the exhaust port. The study was based on kinetic and thermodynamic analysis. Yan Chang et al [13], presented in their technical paper the negative valve overlap was used as an alternative method of dilution in which early exhaust valve closing causes combustion products to be retained in the cylinder and recompressed near top dead center, before being mixed with fresh charge during the intake stroke. The potential for fuel injection during negative valve overlap to extend the dilution limit of spark ignition combustion was evaluated in this work using experiments conducted on a gasoline direct injection engine with variable intake and exhaust valve timing.

Xiangyu Zhang et al [14] presented in their technical paper experiments were conducted to study the effects of five different valve strategies, including three intake valve closure timing strategies and two rebreathing strategies on the combustion and emission characteristics at various low loads on a heavy-duty diesel engine. In order to control the NO<sub>x</sub> emissions within low levels, the externally cooled exhaust gas recirculation was used.

Bernhard Semlitsch et al [15] presented in their technical paper the consequences of the valve and piston motion onto the energy losses and the discharge coefficient. Large Eddy Simulations are performed in a realistic internal combustion geometry using three different modeling strategies that is fixed valve lift and fixed piston, moving piston and fixed valve lift, and moving piston and moving valve, to evaluate the heat losses. The differences in the flow field development with the different modeling approaches was delineated and the dynamic effects onto the primary quantities. Ming Jia et al [16] presented in their technical paper coupling a multi-dimensional computational fluid dynamics code and genetic algorithm, the potential of high-load expansion by using late intake valve closing was explored in a light-duty diesel engine.

Can Cinar et al [17] presented in their technical paper an alternative combustion mode HCCI seems as one of the most effective choice to increase the thermal efficiency and reduce the soot and NO<sub>x</sub> emissions among the other conventional combustion modes. HCCI combustion has common properties which gasoline and diesel engines. In order to obtain HCCI combustion, using variable valve mechanism was found to be the most effective and practical method in spark ignition engines. In this study, four different valve mechanisms were used in order to extend HCCI operating range in a four stroke, single cylinder gasoline engine. The experiments were performed between 800 and 1900 rpm engine speeds.

J.P. Zammit et al [18] presented in their technical paper the influence of early inlet valve closure on emissions, fuel economy and exhaust gas temperature of a turbocharged, multi cylinder common rail direct injection diesel engine and compared with the influence of deactivating two cylinders. inlet valve closing timings were set at up to 60° crank angle degrees earlier than the production setting of 37° after bottom dead centre for the engine. At the earliest timing, effective compression ratio was reduced from 15.2:1 to 13.7:1. The effects on emissions were significant only for EIVC settings at least 40 CA degrees earlier than the production setting, and were sensitive to engine load. At 2 bar brake mean effective pressure and fixed levels of NO<sub>x</sub>, soot emissions were reduced but carbon monoxide and hydrocarbon increased unless fuel rail pressure was reduced. With increasing load, soot reduction diminished.

Kenta Goto et al [19] presented in their technical paper to improve engine torque and specific fuel consumption in a vehicle and experimentally adjusted the valve lift and opening period in rocker arms for testing various follower configurations. Using the follower configuration in a commercially-available rocker arm, we compared four different levels of valve lift and opening period in the intake, and four different levels in the exhaust, making sixteen combinations. utilizing five kinds of modified follower configurations of the rocker arms in the intake, and three in the exhaust and compared twenty four combinations at the speed of 2400rpm. Nobuyuki Tanaka and Akihiko Kawata [20] presented in their technical paper thermal effects control using sodium filled hollow valves in preference to solid valves in order to decrease the exhaust valve temperature. The most common method for detecting the valve temperature was to find the temperature by measuring hardness on valve surface. The hardness test was applicable to the condition up to 800°C. Therefore, this paper presents new techniques for measuring the temperature for sodium-filled valve using infrared thermography and thermocouple as an alternative hardness test. The authors also examined the valve temperatures at a variety of engine speeds and cooling of the sodium-filled valve during engine operation.

## Conclusions:

1. A continuous variable valve lift mechanism for a diesel engine consists of a driving plunger, a driven plunger, a hydraulic cylinder, and a hydraulic oil tank. Simulation was studied between maximum valve lift and rotation angle of driving plunger and the results indicate that the maximum valve lift decreases with increasing rotation angle. Rotating the driving plunger was an effective method to regulate valve lift.

2. In a diesel engine consists of combustion chamber, also having an after treatment device to treat emissions, an intake valve for passing air into the combustion chamber, and an exhaust valve for passing exhaust out of the combustion chamber, a method of operating the engine, wherein the method includes performing at least one combustion in the combustion chamber at a first exhaust valve timing and a first intake valve closure timing; determining a temperature of the exhaust gas that enters the after treatment device; and if the temperature of the exhaust gas is equal to or below a preselected temperature threshold, then performing at least one combustion in the combustion chamber at a second, earlier exhaust valve closure timing and a second later

intake valve opening timing to thereby increase the internal exhaust gas recirculation and the temperature of exhaust emitted by the diesel engine.

## REFERENCES:

- [1] Mateos Kassa, Carrie Hall, Fabien Vidal-Naquet, “Thomas Leroy The Impact of Intake Valve Dynamics on Knock Propensity in a Dual-Fuel SI Engine”, SAE International, **2017-01-2236**
- [2] Xianlin Ouyang, Ho Teng, Xiaochun zeng, Xuwei Luo, Tingjun Hu, Xianlong Huang, Jiankun Luo, Yongli Zhou, “A Comparative Study on Influences of EIVC and LIVC on Fuel Economy of A TGDI Engine Part I: Friction Torques of Intake Cams with Different Profiles and Lifts “, SAE International, 2017-01-2245
- [3] Dojoong Kim, Dong Hyeong Lee, Jong Wung Park, Soo Hyun Hwang, Wan Jae Jeon, “Development of a Two-Step Variable Valve Actuation Mechanism Equipped with an Electronic Switching System”, SAE International, 2017-01-2412
- [4] Luigi Teodosio, Vincenzo De Bellis, Fabio Bozza, Daniela Tufano, “Numerical Study of the Potential of a Variable Compression Ratio Concept Applied to a Downsized Turbocharged VVA Spark Ignition Engine”, SAE International, 2017-24-0015
- [5] Andrea Piano, Federico Millo, Davide Di Nunno, Alessandro Gallone, “Numerical Analysis on the Potential of Different Variable Valve Actuation Strategies on a Light Duty Diesel Engine for Improving Exhaust System Warm Up”, SAE International, 2017-24-0024
- [6].Mirko Baratta, Daniela Misul, Jiajie Xu, Alois Fuerhapter, Rene Heindl, Cesare Peletto, Jean Preuhs, Patrick Salemi, “Development of a High Performance NG Engine Embedding Direct Gas Injection and Variable Valve Actuation”, SAE International, 2017-24-0152
- [7].Igor Trevas, Adm José baeta, Charles Pimenta, Heder Fernandes, Matheus Carvalho, Raphael Montemor , “Combustion Analysis on a Variable Valve Actuation Spark Ignition Engine Operating With E22 and E100”, SAE International, 2017-01-1069
- [8].Guy Babbitt, Jeff Rogers, Kristina Weyer, Drew Cohen, Stephen Charlton, “DigitalAir Camless FVVA System – Part 1, Valve Train Design, Capability and Performance”, SAE International, 2017-01-0635
- [9] Dileep Malkhede, Sudesh Jadhav, Amit Dhotre, “Kinematic Analysis of Continuous Variable Valve Lift Mechanism for SI Engine”, SAE International, 2017-26-0033
- [10]Shinji Kasatori, Yuji Marui, Hideto Oyama, Kosuke Ono, “Development of Heat Resistant Titanium Alloy for Exhaust Valves Applicable for Motorcycles”, SAE International, 2016-32-0023
- [11] José Ramón Serrano, Pedro Piqueras, Roberto Navarro, Javier Gómez, Marc Michel, Bénédicte Thomas, “ Modelling Analysis of Aftertreatment Inlet Temperature Dependence on Exhaust Valve and Ports Design Parameters”, SAE International, 2016-01-0670
- [12] Jorge Martins, Carlos Pereira, F.P. Brito, “A New Rotary Valve for 2-Stroke Engines Enabling Over-Expansion”, SAE International, 2016-01-1054
- [13] Yan Chang, Margaret Wooldridge, Stanislav V. Bohac, “Extending the Dilution Limit of Spark Ignition Combustion via Fuel Injection during Negative Valve Overlap”, SAE International, 2016-01-0671
- [14] Xiangyu Zhang, Hu Wang, Zunqing Zheng, Rolf D. Reitz, Mingfa Yao “Effects of late intake valve closing (LIVC) and rebreathing valve strategies on diesel engine performance and emissions at low loads”, Applied Thermal Engineering, 98(5), 2016, 310-319
- [15] Bernhard Semlitsch, Yue Wang, Mihai Mihescu “Low effects due to valve and piston motion in an internal combustion engine exhaust port”, Energy Conversion and Management, 96(5), 2015, 18-30
- [16] Ming Jia, Yaopeng Li, Maozhao Xie, Tianyou Wang, Hu Wang, Rolf D. Reitz, “The Potential of High-load Extension by Using Late Intake Valve Closing for a Diesel Premixed Charge Compression Ignition Engine”, Energy Procedia, 66, 2015, 33-36
- [17] Can Cinar, Ahmet Uyumaz, Hamit Solmaz, Tolga Topgul, “Effects of valve lift on the combustion and emissions of a HCCI gasoline engine”, Energy Conversion and Management, 94(4), 2015, 159-168
- [18] J.P. Zammit , M.J. McGhee, P.J. Shayler, T. Law, I. Pegg “The effects of early inlet valve closing and cylinder disablement on fuel economy and emissions of a direct injection diesel engine”, Energy, 79 ,2015 100-110
- [19] Kenta Goto, Shinji Noda, Kohei Nakashima, Yoshio Murakami, “Optimizing the Opening Period and the Timing of Intake and Exhaust Valves to Improve Engine Performance in a Supermileage Vehicle”, SAE International, 2015-32-0742
- [20].Nobuyuki Tanaka, Akihiko Kawata “Measurement Technique of Exhaust Valve Temperature”, SAE International, 2015-01-1999
- [21] K Ashok Reddy M Bhagvanth Rao P Ram Reddy “Experimental Estimation of Heat Transfer Coefficients Using Helical Coil in an Agitated Vessel”, International Journal of Engineering Trends and Technology- 3(2) (2012) 113
- [22] K Ashok Reddy M Bhagvanth Rao P Ram Reddy “Determination of Heat Transfer Cooling Rates in an Mixing Vessel Using Kanthal Heating Element” International Journal of Engineering Trends and Technology- 3(2) (2012) 193
- [23] K Ashok Reddy M Bhagvanth Rao P Ram Reddy “ Effect of Dean Number on Heating Transfer Coefficients in an Flat Bottom Agitated Vessel” IOSR Journal of Engineering 2(4) (2012) 945-951
- [24] K Ashok Reddy M Bhagvanth Rao P Ram Reddy “A Review of Nusslet Number under Laminar Flow Condition in Heat Exchanger” IOSR Journal of Mechanical and Civil Engineering 11(2) (2014) p76-80 ISSN : 2278-1684



- [25] Kasi Naga Santhosh Kumar.P, Jeevan Reddy.K, Manoj Kumar.R, Sravan Kumar Reddy.M, and Ashok Reddy K , “Design Analysis of Two Stroke I. C. Engine Powered by Compressed Air”, International Journal of Mechanical Engineering and Research, 3(1) 18-21, 2014
- [26] K. Ashok Reddy, M. Bhagvanth Rao, P. Ram Reddy, “ An Experimental Investigations of Nusselt Number for Low Reynolds Number in an Agitated Helical Coil”, International Journal Of Modern Engineering Research 4(12), 2014 , 35-39
- [27] K Ashok Reddy, M Bhagvanth Rao and P Ram Reddy, “Influence of Power Number on Nusselt Number for Newtonian and Non-Newtonian Fluids in an Un Baffled Agitated Vessel”, IOSR Journal of Mechanical and Civil Engineering, 11(6), 2014, 7-10
- [28] K Ashok Reddy, 2015, “Methods and Materials Characterization of Sodium Carboxymethyl Cellulose”, International Journal of Advanced Research Foundation, 2(1), 2015, 23-26.
- [29] K Ashok Reddy ,2015, “An Alternative Method to Evaluative Nusselt Number in a Helical Coil Heat Exchanger for non Newtonian Fluids ,” International Journal Of Advances in Engineering and Management 2(1), 2015 1-3
- [30] K Ashok Reddy, M Bhagvanth Rao and P Ram Reddy , 2015, “Analysis of Friction Factor for Newtonian and non-Newtonian Fluids in an Mechanically Agitated Vessel,” International Journal Of Advances in Engineering and Management, 2(1), 2015., 1-3
- [31] K Ashok Reddy, “A Critical Review of Nusselt Number and Performance Characteristics of I.C. Diesel Engine Using Alternative BioFuels”, International Journal of Advanced Research Foundation, 2(1), 2015, 31-35.
- [32] S Sathagiri , K Jayathirtha Rao , K Ashok Reddy and C Sharada Prabhakar, “ Comparison of Mechanical Properties on 15CDV6 Steel Plates by TIG- Welding with and without copper coated filler wires”, International Journal of Advanced Research Foundation , 2(5), 2015,16-20
- [33] K. Ashok Reddy, T. V. Seshi Reddy and S Satpagiri , “Heat Flux and Temperature Distribution Analysis of I C Engine Cylinder Head Using ANSYS “,International Journal of Advanced Research Foundation , 2(5), 2015, 21-26.
- [34] K. Ashok Reddy, “ A Critical Review of Heat Transfer Studies in S Shaped Helical Coil Heat Exchanger Using Nano Fluids”, International Journal of Advanced Research Foundation, 2(9), 2015, 5-12
- [35]K. Ashok Reddy, “ A Critical Review of Transmission Loss and Acoustic Methods for Performance Evaluation of Muffler Part-1 ”, International Journal of Advanced Research Foundation, 2 (10), 2015, 1-5
- [36] K. Ashok Reddy, “A Critical Review Of Renewable Solar Energy Applications”, IOSR Journal of Mechanical and Civil Engineering , 15(11), 2015, 20-24
- [37] K Ashok Reddy .Experimental Investigation of Turbulence Flow Creation with Different Profiles in Intake Manifold of Diesel Engine International Journal of Emerging Technology and Advanced Engineering , 6(2), 2016, 244-249
- [38]K Ashok Reddy A Survey Of Entropy Generation In A Helical Coil Heat Exchanger International Journal of Innovative Technology and Exploring Engineering, 5(3), 2016, 2910-2915
- [39] K Ashok Reddy A Critical Review Of Performance Analysis Of Nano Coolants In Diesel Engine International Journal of Engineering, Business and Enterprise Applications, 15(1), 2016 , 95-98
- [40] K Ashok Reddy Taguchi Approach To Evaluate Performance Parameters For Diesel & Petrol Engine International Journal of Current Engineering and Technology, 6(2), 2016, 451-453
- [42] K ashok Reddy A Survey On Combustion Engine Using Compressed Natural Gas-Diesel Fuel System International Journal of Innovative Research in Science ,Engineering and Technology, 5(3), 2016, 3575-3579
- [42] K Ashok Reddy, A Crtical Review Of Entropy Generation in Internal Combustion Engine IPASJ International Journal of Mechanical Engineering , 4(3), 2016, 1-4
- [43].K Ashok Reddy Performance Evaluation of Water Emulsion Fuel used in Internal Combustion Engine International Journal of Advance Engineering and Research Development, 3(3), 2016, 210-214
- [44].K Ashok Reddy, Exhaust Manifold Developmental Activates in Compression Ignition Engine International Journal of Emerging Technologies in Computer and Applied Sciences, 15(1), 2016, 80-85
- [45] K Ashok Reddy A Survey of Entropy Generation in a Helical Coil Heat Exchanger International Journal of Innovative Technology and Exploring Engineering, 5(11), 2016, 1-3
- [46].K Ashok Reddy, “A Critical Review Of Entropy Generation Analysis in Micro Channel Using NanoFluids “, International Journal of Science & Engineering Development Research , 1(5), 2016, 7-12
- [47] K Ashok Reddy, “Developmental Practices Of Intake Manifold For Compression And Spark Ignition Engines”, International Journal of Innovative Research in Science, Engineering and Technology, 5(5), 2016 6638-6644
- [48] K Ashok Reddy , “Performance Analysis and Evaluation of Solar Still System”, International Journal of Emerging Technologies in Computer and Applied Sciences 16(1), 2016, 54-58
- [49] K Ashok Reddy, “A Review of Heat Transfer Studies for Shell & Tube Heat Exchangers”, International Journal of Science & Engineering Development Research 1 (5) , 2016, 68-73
- [50] K Ashok Reddy Design and Analysis of Toroidal Piston Using Ansys Journal of Mechanical Engineering and Applied Mechanics, 1(2) , 2016, 9-21
- [51] K. Ashok Reddy A Critical Review of Vortex Tube Refrigeration System Journal of Industrial Engineering and Its Applications , 1(1) , 2016, 1-15
- [52] K. Ashok Reddy A Comprehensive Study of Acoustic Techniques in Different Mufflers International Journal of Scientific Development and Research , 1(8), 2016, 345-350
- [53] .K.Ashok Reddy , A Critical Review On Hydrogen-Diesel Fuel Mode Compression Ignition Engine International Journal of Application or Innovation in Engineering & Management 5(3), 2016,13-17
- [54] .K.Ashok Reddy, A Critical Review of Exhaust Recirculation Gas System for CI Diesel Engine International Journal of Application or Innovation in Engineering & Management 5(5), 38-42

- [55] K. Ashok Reddy , “A Critical Review of Renewable Solar Energy Applications”, International Journal for Research Trends and Innovation 2(5), 2017, 110-112
- [56] K Ashok Reddy, “A Critical Review of Thermal Waste Heat Recovery Systems,” International Journal for Research Trends and Innovation 2(5), 2017, 113-117
- [57] K Ashok Reddy, “A Critical Review on Thermal Energy Storage Systems’, International Journal for Research Trends and Innovation 2(5), 2017, 118-121
- [58] J. Deekshith , A. Hari Krishna , D. Laxmi Prasanna, Md.Toufeeq & K. Ashok Redd, “ Experimental Performance of Blended Palm Oil in Diesel Engine ,” International Journal for Research Trends and Innovation 2(5), 293-296
- [59] K Ashok Reddy , Heat Exchange Rates of Solar Refrigeration Systems Using Vacuum Tube Collector International Journal of Scientific Development and Research 2(5), 2017, 115-117
- [60] K Ashok Reddy , Heat Transfer Enhancement Studies Of Copper Oxide Nano Fluids in a Round Pipe With Insert, International Journal of Mechanical Engineering and Technology, 8(7), 2017, 397-104
- [61] K.Ashok Reddy, K. Sandeep Kumar, K. Raja sekhar Reddy, V.V.S. Harnadh Prasad & G. Arun Reddy A Critical Review of Composite Materials for Buildings, Thermal, Aerospace and Cryogenic Applications International Journal of Civil Engineering and Technology, 8(7), 2017, 293-300
- [62] M.Mahender Reddy,K. Ashok Reddy, P. Poornima Reddy & N. Santhisree Experimental Analysis of Convective Heat Transfer and Second Law Analysis in a Helical Coil under Turbulent Condition International Journal of Mechanical Engineering and Technology, 8(8), 2017, 293-300
- [63] P.Sunil Kumar, K. Ashok Reddy, V. Mahender Reddy & P. Ram Krishna Reddy Effect of Power Number on Heat Transfer Coefficients in a Helical Coil Heat Exchanger International Journal of Mechanical Engineering and Technology, 8(8), 2017, 107-116
- [64] U. Suhasini & K. Ashok Reddy, A Comprehensive Study on Defects Parameters of Ferrous and Composite Materials Using Non Destructive Testing Methods International Journal for Research Trends and Innovation, 2(8), 2017, 108-111
- [65] K Ashok Reddy, “ Non-Destructive Testing, Evaluation Of Stainless Steel Materials”, Materials Today: Proceedings, 4(8), 2017, 7302-7312
46. K. Ashok Reddy ,”A Critical Review on Acoustic Methods & Materials of a Muffler”, Materials Today: Proceedings 4(8),2017, 7313-7334

