

AI POWERED AUTOMATIC PLANT DISEASE DETECTION AND PRECISION PESTICIDE SPRAYING SYSTEM

Krushna Ravindra Nirmal¹, Satvik Anil Pawar², Rahul Nivrutti Pawar³, Prof. Borkar S.V.⁴

^{1,2,3}Students, Department of E&TC Engineering, Vidya Niketan College of Engineering, Bota, Maharashtra, India

⁴Project Guide, Department of E&TC Engineering, Vidya Niketan College of Engineering, Bota, Maharashtra, India

ABSTRACT

Agriculture remains the backbone of food security and economic stability, yet crop losses due to plant diseases continue to pose a significant global challenge, reducing annual yields by 10% to 40%. Traditional monitoring relies heavily on manual field scouting, which is labor-intensive, subjective, and often too late for effective target intervention, leading to excessive chemical usage. This research paper presents an integrated automated edge solution combining computer vision, deep learning, and robotic precision spraying mechanisms. Deployed on a resource-constrained Raspberry Pi 3 platform, a trained lightweight YOLOv8-Nano model processes real-time leaf images captured via a high-resolution camera module to identify fungal, bacterial, and viral infections. Upon disease confirmation with a confidence score exceeding 0.90, the synchronized on-board system triggers a multi-channel relay array and high-speed solenoid valves, delivering localized pesticide doses tailored to affected foliage sections. Empirical validation confirms a disease classification accuracy of 97.5% on the test dataset and a dramatic 75% reduction in chemical consumption compared to traditional broadcast methods, showcasing an affordable and ecologically sustainable approach toward precision smart farming.

Keywords: Precision Agriculture, Plant Disease Detection, Deep Learning, YOLOv8-Nano, Raspberry Pi, Smart Spraying, Electromechanical Synchronization.

I. INTRODUCTION

The agricultural sector faces a continuous, escalating battle against plant diseases, which directly threaten regional food stability and market predictability. The standard commercial protocol for plant health monitoring relies on visual inspection, which is inherently time-consuming, highly subjective, and prone to human error—especially during early stage symptom development when structural discolorations are subtle. Delayed detection typically triggers a severe over-reactive countermeasure: the indiscriminate, broad-acre broadcast application of high-concentration pesticides.

This continuous blanket chemical spraying presents extensive environmental crises, including chemical contamination of groundwater tables, degradation of soil microbial health, and high biological chemical resistance across destructive target pathogens. Financially, it forces an unsustainable overhead burden on small-to-medium scale farming groups due to massive product waste.

The motivation of this research is to leverage modern advancements in Edge Artificial Intelligence (AI) and automated electromechanical systems to instantiate an autonomous 'see-and-spray' robotic vehicle. By shifting treatment paradigms from field-wide broadcast logic to plant-level localized spot-spraying, the system ensures optimal ecological protection, maximized crop survival, and minimized chemical deployment cost.

Project Objectives:

- Design and assemble an agile, four-wheel autonomous differential platform optimized for field row navigation.
- Deploy a highly optimized deep learning architecture (YOLOv8-Nano) onto an edge device (Raspberry Pi 3 Model B+) for real-time plant leaf diagnosis.
- Integrate a high-speed spraying control assembly (submersible DC pumps and solenoid valves) to execute real-time targeted pesticide release.

- Target a minimum threshold classification performance accuracy of 95% under varying real-world field illuminations.
- Achieve a quantifiable, verifiable drop in active pesticide volume utilization compared to conventional broadcast metrics.

II. LITERATURE REVIEW

Deep Learning in Plant Disease Detection

Agricultural monitoring has rapidly transitioned from manual feature extraction frameworks (such as Scale-Invariant Feature Transform—SIFT, and Histograms of Oriented Gradients—HOG) toward robust Convolutional Neural Networks (CNNs). Benchmark research by Mohanty et al. (2016) utilized deep architectures including AlexNet and GoogLeNet on the standardized PlantVillage dataset, verifying classification metrics exceeding 99% accuracy under strict laboratory contexts.

However, traditional image classification models lack localized awareness—they classify an entire image block rather than identifying specific micro-regions of infection on an individual leaf. Consequently, modern precision agriculture has integrated real-time object detection models. The You Only Look Once (YOLO) framework series, specifically YOLOv8-Nano, offers an optimized mathematical topology providing high mean Average Precision (mAP) alongside rapid inference speeds, making it uniquely qualified for low-power edge microprocessors.

Precision Spraying Robotics

Automated site-specific agrochemical application has advanced from baseline sensor configurations (such as standard chlorophyll sensors) to advanced vision-guided intelligence. Early structural frameworks utilized static preset GPS boundaries and predefined prescription mapping indices to alter flow rates across broad fields. Modern paradigms emphasize active real-time visual synchronization. Realizing this 'see-and-spray' concept requires minimizing latency gaps between image execution, algorithm processing, and physical actuator triggering. Research highlights that vehicle ground speed, camera line-of-sight orientations, and valve response rates must form a structurally cohesive loop to ensure fluid drop accuracy hits the identified infected surface zone exactly.

III. METHODOLOGY

The operational infrastructure of the proposed system is segmented into three interconnected structural units: the Robotic Mobility Platform, the Vision Processing Engine, and the Precision Actuation Array.

A. Hardware Infrastructure & Component Interfacing

The hardware ecosystem centers around a Raspberry Pi 3 Model B+, balancing compute resource requirements with energy conservation. Because the microprocessor's native GPIO lines output at a low-current 3.3V logic ceiling, specialized high-isolation interface electronics are leveraged to safely bridge control signals to high-power mechanical nodes.

Component Element	Interface Node / Protocol	System Functionality
Raspberry Pi Camera Module v2	CSI (Camera Serial Interface) Port	Real-time high-resolution image stream acquisition.
L298N H-Bridge Motor Driver	4 Digital GPIO Pins (PWM Enabled)	Directional and velocity control for DC Geared Motors.
Multi-Channel Relay Module (5V)	3 Digital Output GPIO Pins	Isolated electronic switching for the fluid pump units.
Submersible DC Pumps (x3)	Relay Interfaced Output Line	Fluid draw from dedicated pesticide storage tanks.
High-Speed Solenoid Valve (12V)	Power MOSFET / Relay Connection	Millisecond-level precision spray gating control.

Table 1: Hardware Component Interfacing and Node Configuration Matrix

B. Software Architecture and Control Flow

The operational control loop runs continuously on-device using a Python-based implementation optimized with the OpenCV and TensorFlow Lite runtime engines. The execution logic proceeds through the following sequential algorithmic pipeline:

- **Frame Capture:** The camera pulls an active RGB video frame via the high-speed CSI interface link.
- **Pre-processing:** Spatial dimension rescaling reshapes the incoming matrix to an optimized resolution of 416 x 416 pixels, followed by float normalization.
- **TFLite Inference Execution:** The matrix is evaluated through the embedded YOLOv8-Nano TFLite network structure.
- **Threshold Decision Matrix:** If a targeted disease state matches with a prediction confidence threshold exceeding 90% ($C_score > 0.90$), the bounding box coordinates are mapped.
- **Dynamic Spray Computation:** The system automatically extracts the current forward locomotion velocity index, determines the spatial area offset, and calculates the target solenoid gating opening time window (T_spray).
- **Actuator Release:** The GPIO signal changes state, causing the relay to close and firing a highly targeted spray burst onto the infected region without halting forward movement.

IV. DESIGN CALCULATIONS

Mathematical precision across design variables is mandatory to ensure that the robotic platform's movement matches the vision computation pipeline, ensuring zero fluid distribution misalignment.

A. Mobility, Kinematics, and System Latency Tracking

To preserve image frame clarity and eliminate motion-induced spatial blur, the linear movement velocity must be structurally bound by both the inference loop period and camera Field-Of-View (FOV) limits.

Given a predefined maximum design linear field speed of $v = 0.5$ m/s and an outer wheel diameter specification of $D_w = 0.065$ m (radius $r = 0.0325$ m), the wheel's required angular parameters are computed as follows:

$$\text{Angular Velocity: } \omega = v / r = 0.5 \text{ m/s} / 0.0325 \text{ m} = 15.38 \text{ rad/s}$$

$$\text{Rotational Speed: RPM} = (\omega / 2\pi) \times 60 = (15.38 / 6.283) \times 60 \approx 146.9 \text{ RPM}$$

The system loop performance index defines the maximum distance the physical robot can traverse during an active computational cycle. With an empirical on-board edge inference delay tracked at $T_inference = 0.2$ seconds (producing a real-time output scale of roughly 5 FPS), the maximum forward distance offset per cycle (d_max) yields:

$$d_max = v \times T_inference = 0.5 \text{ m/s} \times 0.2 \text{ s} = 0.1 \text{ m} = 10 \text{ cm}$$

Because the camera module's target lens Field of View covers a longitudinal ground path span of 20 to 30 cm at operational height, a cycle travel window of 10 cm ensures substantial frame-to-frame spatial overlap, ensuring zero plant areas are skipped during forward travel.

B. Spray Volume Dosage and Actuator Duration Tuning

The core goal is to apply a minimal fluid volume (V_dose) to the infected target region (A_detect), achieving uniform droplet coverage while eliminating chemical runoff.

The integrated DC pump maintains an operational delivery ceiling of $Q_max = 1.5$ L/min. Accounting for internal line pressure drops and nozzle design restrictions, the effective continuous discharge rate through the spray tip is fixed at $Q_spray = 1.0$ L/min, which translates to:

$$Q_spray = 1000 \text{ mL} / 60 \text{ s} \approx 16.67 \text{ mL/s}$$

For a representative infected leaf cluster area measuring $A_leaf = 50$ cm² demanding an agronomic target pesticide concentration profile of $D_target = 0.05$ mL/cm², the target dosage volume and required valve open duration (T_spray) are calculated as:

$$\text{Target Delivery Volume: } V_dose = A_leaf \times D_target = 50 \text{ cm}^2 \times 0.05 \text{ mL/cm}^2 = 2.5 \text{ mL}$$

$$\text{Required Solenoid Open Time: } T_spray = V_dose / Q_spray = 2.5 \text{ mL} / 16.67 \text{ mL/s} \approx 0.15 \text{ s (150 ms)}$$

This millisecond-level precision timing is directly enforced via GPIO pin state timing control, producing an extremely focused, localized burst of pesticide targeted to the infected region.

V. RESULTS, TESTING, AND VALIDATION

A. AI Model Diagnostic Performance

The model pipeline was trained off-board utilizing public PlantVillage image arrays augmented with local real-world crop leaf profiles, and compiled into a localized TFLite structure. Evaluation on a dedicated validation set confirms strong classification metrics across all target categories.

Crop & Disease Class Category	Precision Profile	Recall Index	F1-Score Metric	Overall Accuracy
Tomato - Healthy	0.98	0.99	0.98	98.5%
Tomato - Early Blight	0.96	0.95	0.95	95.8%
Tomato - Late Blight	0.95	0.97	0.96	96.2%
Tomato - Leaf Mold	0.97	0.94	0.95	95.5%
System Test Average	0.965	0.962	0.960	97.5%

Table 2: Deep Learning Confusion Matrix and Model Validation Metrics Breakdown

B. Integrated System Synchronization and Chemical Conservation Profile

Field testing focused on validating physical spray alignment accuracy during active forward travel. The geometric distance offset between the center of a simulated leaf disease spot and the actual center of the fluid spray impact zone was precisely mapped.

The physical spatial nozzle alignment offset was configured at 10 cm behind the optical lens center line. This geometric offset serves as an internal mechanical buffer, compensating for the 200 ms computational processing latency and internal solenoid valve activation delays. Across repeated operational trial runs at full field velocity, the physical droplet targeting deviation error was consistently bound within a tight error margin of 1.5 ± 0.5 cm.

Treatment Methodology	Pesticide Volume Used per Plot	Average Targeting Precision Error	Runoff & Eco-Waste Index
Traditional Manual Broadcast Method	4.0 Liters	N/A (Total Blanket Application)	High / Severe Runoff Risk
AI-Powered Precision Spot Spraying	1.0 Liter	1.5 cm Spatial Tracking Margin	Negligible / Confined to Target Leaf
<i>Net Improvement Summary</i>	<i>75.0% Volume Reduction</i>	<i>Centimeter-Level Targeting Control</i>	<i>Elimination of Broad Soil Toxicity</i>

Table 3: Agro-Chemical Consumption and Efficiency Validation Matrix

VI. CONCLUSION AND FUTURE SCOPE

This research successfully demonstrates an automated, cost-efficient, edge-computing agricultural solution for automated leaf disease identification and precision pesticide application. By compiling an optimized YOLOv8-Nano framework into an active TensorFlow Lite model deployed on a Raspberry Pi 3 microcontroller, the prototype achieved a high disease classification accuracy of 97.5%. More importantly, under real field constraints, the system maintained an exceptionally tight 1.5 cm physical spray impact alignment margin. The resulting 75% drop in total pesticide volume consumption proves the massive economic and environmental value of transitioning toward localized computer-vision-driven crop care.

Future system enhancements will focus on deploying multispectral camera assemblies to detect internal crop tissue degradation before symptoms become visible to the naked eye. Additionally, integrating RTK-GPS modules and LiDAR sensors will enable autonomous row navigation across complex farm terrains, and cloud-linked IoT modules can automatically map real-time field disease outbreaks for large-scale farm management.

REFERENCES

- [1] Mohanty, S. P., Hughes, D. P., & Salathé, M. (2016). 'Using Deep Learning for Image-Based Plant Disease Detection.' *Frontiers in Plant Science*, Vol. 7, Article 1419.
- [2] Zhang, X., Han, L., Dong, Y., Hong, Y., & Sun, J. (2020). 'An adaptive target location and spray system for orchards based on deep learning.' *Computers and Electronics in Agriculture*, Vol. 173, p. 105436.
- [3] Mayer, R., and Spidell, K. J. (2018). 'Review of Autonomous Variable-Rate Application Systems and Precision Agricultural Robotic Platforms.' *Journal of Agricultural Engineering Research*, Vol. 45, pp. 112-124.
- [4] Raspberry Pi Foundation (2018). 'Raspberry Pi 3 Model B+ Technical Product Documentation and GPIO Hardware Layer Specification Sheets.' Technical Report Series Reference RPi-3B-Rev1.
- [5] STMicroelectronics (2000). 'L298 Dual Full-Bridge Driver Technical Datasheet and Power Isolation Control Guidelines.' ST Semiconductor Component Catalog, pp. 1-14.



IJRTI